

B
Type

Docs

13
Plans

BLD04-3138
Building Permit Number (List all associated with these documents)

5987
Street Number

LONE PINE Rd.
Street Name

Hes
Community Code


063-090-050
APN

SHEET NUMBERED NOTES

- 1 COUNTER TOP.
- 2 DUAL KITCHEN SINK IV GARBAGE DISPOSAL.
- 3 PEDESTAL BATHROOM SINK.
- 4 LOW FLOW TOILET.
- 5 36" X 42" TILED SHOWER IV TEMPERED GLASS FRONT AND DOOR. PROVIDE WATER GYP. BOARD FROM FLOOR TO CEILING IN ENCLOSURE AREA.
- 6 LINEN CLOSET IV (5) ADJUSTABLE SHELVES.
- 7 STACKED WASHER/DRYER UNIT.
- 8 WATER HEATER IV PRESSURE RELIEF VALVE DRAINED TO OUTSIDE. PROVIDE COMBUSTION AIR & VENTING TO COMPLY IV CHAPTER 15 OF THE UNIFORM PLUMBING CODE.
- 9 BUILT-IN MURPHY BED WALL UNIT.
- 10 BUILT-IN CABINET IV (3) SHELVES & DOOR TO 56" A.F.F. & (3) OPEN SHELVES ABOVE.
- 11 36" COOK TOP IV DOWN DRAFT.
- 12 BUILT-IN WALL UNIT IV (2) SHELVES & PRL OF DOORS TO 30" A.F.F. & (4) SHELVES ABOVE.
- 13 OPEN SHELVING BELOW COUNTER IV (2) SHELVES.
- 14 SOLID CORE FIRE RATED DOOR IV AUTO-CLOSING HINGES.
- 15 5/8" TYPE "X" GYP. BD. @ ALL GARAGE WALLS & CEILING IV 6d CURHEAD NAILS @ 6" O.C.
- 16 REFRIGERATOR; BUILT-IN.
- 17 DISHWASHER.

NOTE:

PROVIDE SPRINKLER SYSTEM PER FIRE SAFE STANDARDS. (BY OTHERS)



FLOOR PLAN

SCALE 1/4" = 1'-0"



TOTAL LIVING AREA (CONDITIONED)	821.22	SQ. FT.
TOTAL GARAGE AREA (NON-CONDITIONED)	348.25	SQ. FT.
TOTAL COVERED PORCH AREA (NON-CONDITIONED)	19.38	SQ. FT.
TOTAL BUILDING FOOTPRINT	1294.00	SQ. FT.

PLOT DATES	
TRACED SET	10/1/04
REVISED 1	10/1/04
REVISED 2	10/1/04
REVISED 3	10/1/04
REVISED 4	10/1/04
REVISED 5	10/1/04
REVISED 6	10/1/04
REVISED 7	10/1/04
REVISED 8	10/1/04
REVISED 9	10/1/04
REVISED 10	10/1/04
REVISED 11	10/1/04
REVISED 12	10/1/04
REVISED 13	10/1/04
REVISED 14	10/1/04
REVISED 15	10/1/04
REVISED 16	10/1/04
REVISED 17	10/1/04
REVISED 18	10/1/04
REVISED 19	10/1/04
REVISED 20	10/1/04
REVISED 21	10/1/04
REVISED 22	10/1/04
REVISED 23	10/1/04
REVISED 24	10/1/04
REVISED 25	10/1/04
REVISED 26	10/1/04
REVISED 27	10/1/04
REVISED 28	10/1/04
REVISED 29	10/1/04
REVISED 30	10/1/04
REVISED 31	10/1/04
REVISED 32	10/1/04
REVISED 33	10/1/04
REVISED 34	10/1/04
REVISED 35	10/1/04
REVISED 36	10/1/04
REVISED 37	10/1/04
REVISED 38	10/1/04
REVISED 39	10/1/04
REVISED 40	10/1/04
REVISED 41	10/1/04
REVISED 42	10/1/04
REVISED 43	10/1/04
REVISED 44	10/1/04
REVISED 45	10/1/04
REVISED 46	10/1/04
REVISED 47	10/1/04
REVISED 48	10/1/04
REVISED 49	10/1/04
REVISED 50	10/1/04
REVISED 51	10/1/04
REVISED 52	10/1/04
REVISED 53	10/1/04
REVISED 54	10/1/04
REVISED 55	10/1/04
REVISED 56	10/1/04
REVISED 57	10/1/04
REVISED 58	10/1/04
REVISED 59	10/1/04
REVISED 60	10/1/04
REVISED 61	10/1/04
REVISED 62	10/1/04
REVISED 63	10/1/04
REVISED 64	10/1/04
REVISED 65	10/1/04
REVISED 66	10/1/04
REVISED 67	10/1/04
REVISED 68	10/1/04
REVISED 69	10/1/04
REVISED 70	10/1/04
REVISED 71	10/1/04
REVISED 72	10/1/04
REVISED 73	10/1/04
REVISED 74	10/1/04
REVISED 75	10/1/04
REVISED 76	10/1/04
REVISED 77	10/1/04
REVISED 78	10/1/04
REVISED 79	10/1/04
REVISED 80	10/1/04
REVISED 81	10/1/04
REVISED 82	10/1/04
REVISED 83	10/1/04
REVISED 84	10/1/04
REVISED 85	10/1/04
REVISED 86	10/1/04
REVISED 87	10/1/04
REVISED 88	10/1/04
REVISED 89	10/1/04
REVISED 90	10/1/04
REVISED 91	10/1/04
REVISED 92	10/1/04
REVISED 93	10/1/04
REVISED 94	10/1/04
REVISED 95	10/1/04
REVISED 96	10/1/04
REVISED 97	10/1/04
REVISED 98	10/1/04
REVISED 99	10/1/04
REVISED 100	10/1/04

DESIGNER OF RECORD
KURT E. GIUSTI
RESIDENTIAL DESIGN & PLANNING
BOX 128 FORESTVILLE, CA 95456 707.667.9522


CLIENT'S
PHILIP AND SUSAN NIX
5985 LONE PINE ROAD SEBASTOPOL, CALIFORNIA 95472 BARN CONVERSION
DESCRIPTION
FLOOR PLAN

ENGINEER OF RECORD
SCOTT HUNTER Ph.D., P.E.
927 STEWART STREET #3 SANTA ROSA, CA 95404
707-528-8435

DESCRIPTION
FLOOR PLAN
SHEET
2
SCALE 1/4" = 1'-0"
OP 13

SHEET NUMBERED NOTES

1. GLASS "A" CORRUGATED METAL ROOFING. INSTALL PER MANUFACTURER.
2. ALL GUTTERS ARE TO BE 5" O.D. SEAMLESS 26 GA. G.S. WITH BAKED ENAMEL FINISH. DOWNSPOUTS ARE TO MATCH.
3. 2' X 4' SKYLITE ON 2X6 MOOD FRAMED CURB IV METAL FLASHING PER METAL ROOFING/SKYLIGHT MANUFACTURERS.
4. CONTINUOUS RIDGE VENT PER ROOFING MANUFACTURER.
5. R.V. TRELLIS. SEE ROOF FRAMING PLAN FOR DETAILS.
6. CONNECT ALL DOWNSPOUTS TO A 4" DIA. SUBTERRANEAN NON-PERFORATED PIPE SLOPED 1/4" PER FOOT MINIMUM TO DRAIN TO DAYLIGHT AT LEAST 12 FEET AWAY FROM ALL STRUCTURES.
7. ALL ROOF FLASHING SHALL BE FABRICATED OUT OF 24 GA. G.S. PER DESIGN STANDARDS AND DETAILS FOUND IN THE 1988 FIFTH EDITION OF THE "ARCHITECTURAL SHEET METAL MANUAL" PUBLISHED BY SHAWNA.
8. PLYWOOD SOFFIT AT EAVES AND OVER HANGS. VENT EAVES AS REQUIRED.



ROOF PLAN

SCALE 1/4" = 1'-0"



PLOT DATES	
DRAFT 8/07	
REVISION 1	
REVISION 2	
SUBMITTED	
REVISION 1	
REVISION 2	
REVISION 1	
REVISION 2	

JOB #	20
DRAWN BY	

DESIGNER OF RECORD

KURT E. GIUSTI
RESIDENTIAL DESIGN
& PLANNING
BOX 128
FORESTVILLE, CA 95456
707.887.8522

CLIENT/S

PHILIP AND SUSAN NIX
5985 LONE PINE ROAD
SEBASTOPOL, CALIFORNIA 95472
BARN CONVERSION

DESCRIPTION

ROOF PLAN

ENGINEER OF RECORD

SCOTT HUNTER Ph.D., P.E.
927 STEWART STREET #3
SANTA ROSA, CA 95404
707-526-6435


DESCRIPTION

ROOF PLAN

SCALE 1/4" = 1'-0"


3

OF 13



NORTH ELEVATION

SCALE 1/4" = 1'-0"



EAST ELEVATION


SCALE 1/4" = 1'-0"

SHEET NUMBERED NOTES

1. 1X LAP SIDING O/ PLYND SHEAR PANELING.
2. 6.5M. SEAMLESS BUTTER.
3. GLASS 7A" CORRUGATED MTL. ROOFING.
4. SKYLIGHT: INSTALL PER MANUF.
5. CONTINUOUS RIDGE VENT.
6. 1X R/X TRIM.
7. DUAL GLAZED WOOD WINDOWS.
8. DECORATIVE DOOR W/ VERT. 1X6 R/X O/ BLDG. PAPER AND TYP. PLYND SHEAR PANELING.


9. DECORATIVE HALF DOOR W/ VERT. 1X6 R/X O/ BLDG. PAPER AND TYP. PLYND SHEAR PANELING.
10. GARAGE DOOR W/ VERT. 1X6 R/X SIDING VENEER O/ PLYND & 2X CONSTRUCTION.
11. 1X6 R/X TRIM @ TOP OF WALL @ GABLE ENDS.
12. 2X6 R/X BARGE RAFTER.
13. NOT USED.
14. TAIL END OF 5-1/8"X10-1/2" 6LB. RIDGE BEAM EXTENDED 6" BEYOND BARGE RAFTER.

15. 1X6 R/X TRIM @ HEAVERS, TYP.
16. 1X4 R/X TRIM @ DOOR/WINDOW SIDES, TYP.
17. 2X2 R/X DECORATIVE SILL, TYP.
18. 1X6 R/X TRIM AT APRONS, TYP.
19. 1X6 R/X TRIM @ CORNERS, TYP.
20. OUTLINE OF R/X TRIM IS SHOWN DASHED FOR CLARITY.



SOUTH ELEVATION

SCALE 1/4" = 1'-0"



WEST ELEVATION

SCALE 1/4" = 1'-0"

PLOT DATES	
DRAWN SET	2017.07.20
REVISED 1	
REVISED 2	
REVISED 3	
REVISED 4	
REVISED 5	
REVISED 6	
REVISED 7	
REVISED 8	
REVISED 9	
REVISED 10	
REVISED 11	
REVISED 12	
REVISED 13	
REVISED 14	
REVISED 15	
REVISED 16	
REVISED 17	
REVISED 18	
REVISED 19	
REVISED 20	
REVISED 21	
REVISED 22	
REVISED 23	
REVISED 24	
REVISED 25	
REVISED 26	
REVISED 27	
REVISED 28	
REVISED 29	
REVISED 30	
REVISED 31	
REVISED 32	
REVISED 33	
REVISED 34	
REVISED 35	
REVISED 36	
REVISED 37	
REVISED 38	
REVISED 39	
REVISED 40	
REVISED 41	
REVISED 42	
REVISED 43	
REVISED 44	
REVISED 45	
REVISED 46	
REVISED 47	
REVISED 48	
REVISED 49	
REVISED 50	
REVISED 51	
REVISED 52	
REVISED 53	
REVISED 54	
REVISED 55	
REVISED 56	
REVISED 57	
REVISED 58	
REVISED 59	
REVISED 60	
REVISED 61	
REVISED 62	
REVISED 63	
REVISED 64	
REVISED 65	
REVISED 66	
REVISED 67	
REVISED 68	
REVISED 69	
REVISED 70	
REVISED 71	
REVISED 72	
REVISED 73	
REVISED 74	
REVISED 75	
REVISED 76	
REVISED 77	
REVISED 78	
REVISED 79	
REVISED 80	
REVISED 81	
REVISED 82	
REVISED 83	
REVISED 84	
REVISED 85	
REVISED 86	
REVISED 87	
REVISED 88	
REVISED 89	
REVISED 90	
REVISED 91	
REVISED 92	
REVISED 93	
REVISED 94	
REVISED 95	
REVISED 96	
REVISED 97	
REVISED 98	
REVISED 99	
REVISED 100	

DESIGNER OF RECORD

KURT E. GIUSTI

RESIDENTIAL DESIGN
& PLANNING

BOX 128
FORESTVILLE, CA 959456
707.687.8522

CLIENT/S

PHILIP AND SUSAN NIX
5985 LONE PINE ROAD
SEBASTOPOL, CALIFORNIA 95472
BARN CONVERSION

DESCRIPTION ELEVATIONS

ENGINEER OF RECORD

SCOTT HUNTER Ph.D., P.E.
927 STEWART STREET #3
SANTA ROSA, CA 95404

707-526-6435

DESCRIPTION
ELEVATIONS


SHEET

4

SCALE 1/4" = 1'-0"


OP

13




SECTION C-C

SCALE 1/4" = 1'-0"



SECTION B-B

SCALE 1/4" = 1'-0"



SECTION A-A

SCALE 1/4" = 1'-0"

PLOT DATES	
DATE SET	DATE
REVISED 1	REVISED 1
REVISED 2	REVISED 2
REVISED 3	REVISED 3
REVISED 4	REVISED 4
REVISED 5	REVISED 5
REVISED 6	REVISED 6
REVISED 7	REVISED 7
REVISED 8	REVISED 8
REVISED 9	REVISED 9
REVISED 10	REVISED 10
REVISED 11	REVISED 11
REVISED 12	REVISED 12
REVISED 13	REVISED 13
REVISED 14	REVISED 14
REVISED 15	REVISED 15
REVISED 16	REVISED 16
REVISED 17	REVISED 17
REVISED 18	REVISED 18
REVISED 19	REVISED 19
REVISED 20	REVISED 20
REVISED 21	REVISED 21
REVISED 22	REVISED 22
REVISED 23	REVISED 23
REVISED 24	REVISED 24
REVISED 25	REVISED 25
REVISED 26	REVISED 26
REVISED 27	REVISED 27
REVISED 28	REVISED 28
REVISED 29	REVISED 29
REVISED 30	REVISED 30
REVISED 31	REVISED 31
REVISED 32	REVISED 32
REVISED 33	REVISED 33
REVISED 34	REVISED 34
REVISED 35	REVISED 35
REVISED 36	REVISED 36
REVISED 37	REVISED 37
REVISED 38	REVISED 38
REVISED 39	REVISED 39
REVISED 40	REVISED 40
REVISED 41	REVISED 41
REVISED 42	REVISED 42
REVISED 43	REVISED 43
REVISED 44	REVISED 44
REVISED 45	REVISED 45
REVISED 46	REVISED 46
REVISED 47	REVISED 47
REVISED 48	REVISED 48
REVISED 49	REVISED 49
REVISED 50	REVISED 50
REVISED 51	REVISED 51
REVISED 52	REVISED 52
REVISED 53	REVISED 53
REVISED 54	REVISED 54
REVISED 55	REVISED 55
REVISED 56	REVISED 56
REVISED 57	REVISED 57
REVISED 58	REVISED 58
REVISED 59	REVISED 59
REVISED 60	REVISED 60
REVISED 61	REVISED 61
REVISED 62	REVISED 62
REVISED 63	REVISED 63
REVISED 64	REVISED 64
REVISED 65	REVISED 65
REVISED 66	REVISED 66
REVISED 67	REVISED 67
REVISED 68	REVISED 68
REVISED 69	REVISED 69
REVISED 70	REVISED 70
REVISED 71	REVISED 71
REVISED 72	REVISED 72
REVISED 73	REVISED 73
REVISED 74	REVISED 74
REVISED 75	REVISED 75
REVISED 76	REVISED 76
REVISED 77	REVISED 77
REVISED 78	REVISED 78
REVISED 79	REVISED 79
REVISED 80	REVISED 80
REVISED 81	REVISED 81
REVISED 82	REVISED 82
REVISED 83	REVISED 83
REVISED 84	REVISED 84
REVISED 85	REVISED 85
REVISED 86	REVISED 86
REVISED 87	REVISED 87
REVISED 88	REVISED 88
REVISED 89	REVISED 89
REVISED 90	REVISED 90
REVISED 91	REVISED 91
REVISED 92	REVISED 92
REVISED 93	REVISED 93
REVISED 94	REVISED 94
REVISED 95	REVISED 95
REVISED 96	REVISED 96
REVISED 97	REVISED 97
REVISED 98	REVISED 98
REVISED 99	REVISED 99
REVISED 100	REVISED 100

DESIGNER OF RECORD

KURT E. GIUSTI

RESIDENTIAL DESIGN
& PLANNING

BOX 128
FORESTVILLE, CA 95456
707.887.8522

CLIENT/S
PHILIP AND SUSAN NIX
5985 LONE PINE ROAD
SEBASTOPOL, CALIFORNIA 95472
BARN CONVERSION

DESCRIPTION SECTIONS

ENGINEER OF RECORD

SCOTT HUNTER P.H.D., P.E.


927 STEWART STREET, #3
SANTA ROSA, CA 95404

707-526-6436

DESCRIPTION SHEET

SECTIONS	SHEET
	5
SCALE 1/4" = 1'-0"	OF 13

-SEE SHEAR WALL SCHEDULE /
SHEET S1.0 FOR SHEAR WALL
INFORMATION.




SCALE 1/4" = 1'-0"



DESCRIPTION	SHEET
FOUNDATION PLAN	6
SCALE: $1/4" = 1' - 0"$	OF 13

ROOF VENTILATION SCHEDULE:
 REG'D. ATTIC VENTILATION:
 1294.00 SQ.FT. ENCLOSED ROOF / 300 = 4.31 SQ.FT. TOTAL
 2.07 SQ.FT. VENT AT EAVE REG'D. & 2.07 SQ.FT. VENT
 ABOVE ATTIC MID-POINT REG'D.
 VENTILATION TO BE PROVIDED BY:
 (2) - 2 1/2" DIA. HOLES + 0.0682 SQ.FT. VENT (EVERY EAVE BLK &)
 X 30 BLOCKS FOR EVERY BLOCK VENTING
 2.046 G.F.T. AT EAVE



ROOF FRAMING PLAN

SCALE 1/4" = 1'-0"



PLOT DATES	
DATE SET	DATE
REVISED 1	REVISED 1
REVISED 2	REVISED 2
REVISED 3	REVISED 3
REVISED 4	REVISED 4
REVISED 5	REVISED 5
REVISED 6	REVISED 6
REVISED 7	REVISED 7
REVISED 8	REVISED 8
REVISED 9	REVISED 9
REVISED 10	REVISED 10
REVISED 11	REVISED 11
REVISED 12	REVISED 12
REVISED 13	REVISED 13
REVISED 14	REVISED 14
REVISED 15	REVISED 15
REVISED 16	REVISED 16
REVISED 17	REVISED 17
REVISED 18	REVISED 18
REVISED 19	REVISED 19
REVISED 20	REVISED 20
REVISED 21	REVISED 21
REVISED 22	REVISED 22
REVISED 23	REVISED 23
REVISED 24	REVISED 24
REVISED 25	REVISED 25
REVISED 26	REVISED 26
REVISED 27	REVISED 27
REVISED 28	REVISED 28
REVISED 29	REVISED 29
REVISED 30	REVISED 30
REVISED 31	REVISED 31
REVISED 32	REVISED 32
REVISED 33	REVISED 33
REVISED 34	REVISED 34
REVISED 35	REVISED 35
REVISED 36	REVISED 36
REVISED 37	REVISED 37
REVISED 38	REVISED 38
REVISED 39	REVISED 39
REVISED 40	REVISED 40
REVISED 41	REVISED 41
REVISED 42	REVISED 42
REVISED 43	REVISED 43
REVISED 44	REVISED 44
REVISED 45	REVISED 45
REVISED 46	REVISED 46
REVISED 47	REVISED 47
REVISED 48	REVISED 48
REVISED 49	REVISED 49
REVISED 50	REVISED 50
REVISED 51	REVISED 51
REVISED 52	REVISED 52
REVISED 53	REVISED 53
REVISED 54	REVISED 54
REVISED 55	REVISED 55
REVISED 56	REVISED 56
REVISED 57	REVISED 57
REVISED 58	REVISED 58
REVISED 59	REVISED 59
REVISED 60	REVISED 60
REVISED 61	REVISED 61
REVISED 62	REVISED 62
REVISED 63	REVISED 63
REVISED 64	REVISED 64
REVISED 65	REVISED 65
REVISED 66	REVISED 66
REVISED 67	REVISED 67
REVISED 68	REVISED 68
REVISED 69	REVISED 69
REVISED 70	REVISED 70
REVISED 71	REVISED 71
REVISED 72	REVISED 72
REVISED 73	REVISED 73
REVISED 74	REVISED 74
REVISED 75	REVISED 75
REVISED 76	REVISED 76
REVISED 77	REVISED 77
REVISED 78	REVISED 78
REVISED 79	REVISED 79
REVISED 80	REVISED 80
REVISED 81	REVISED 81
REVISED 82	REVISED 82
REVISED 83	REVISED 83
REVISED 84	REVISED 84
REVISED 85	REVISED 85
REVISED 86	REVISED 86
REVISED 87	REVISED 87
REVISED 88	REVISED 88
REVISED 89	REVISED 89
REVISED 90	REVISED 90
REVISED 91	REVISED 91
REVISED 92	REVISED 92
REVISED 93	REVISED 93
REVISED 94	REVISED 94
REVISED 95	REVISED 95
REVISED 96	REVISED 96
REVISED 97	REVISED 97
REVISED 98	REVISED 98
REVISED 99	REVISED 99
REVISED 100	REVISED 100

DESIGNER OF RECORD
 KURT E. GIUSTI
 RESIDENTIAL DESIGN
 & PLANNING
 BOX 128
 FORESTVILLE, CA 95456
 707.857.8522

CLIENT'S
 PHILIP AND SUSAN NIX
 5985 LONE PINE ROAD
 SEBASTOPOL, CALIFORNIA 95472
 BARN CONVERSION
 DESCRIPTION ROOF FRAMING PLAN

ENGINEER OF RECORD
 SCOTT HUNTER Ph.D., P.E.
 927 STEWART STREET #3
 SANTA ROSA, CA 95404
 707-526-6435

DESCRIPTION ROOF FRAMING PLAN
 SHEET
 7
 SCALE 1/4" = 1'-0" OF 13

	DETAIL @ TRUSS	1" = 1'-0"	17		KNEE BRACE SEAT	3" = 1'-0"	13		ROOF @ RIDGE	1" = 1'-0"	9		ROOF @ EXT. WALL	1" = 1'-0"	5		CONC. FTG. @ PERIMETER	1" = 1'-0"	1
	DETAIL @ TRUSS	1" = 1'-0"	18		TRELLIS RAFTER SEAT	3" = 1'-0"	14		TRELLIS BEAM @ POST	1-1/2" = 1'-0"	10		ROOF @ GABLE END	1" = 1'-0"	6		CONC. FTG. @ PERIMETER	1" = 1'-0"	2
	DETAIL @ TRUSS	1" = 1'-0"	19		TRELLIS POST PEDESTAL	1" = 1'-0"	15		TRELLIS CONNECTOR	3" = 1'-0"	11		ROOF @ INT. BEAM	1" = 1'-0"	7		CONC. FTG. @ INTERIOR	1" = 1'-0"	3
NOT USED	NOT USED	-	20		CONC. PATIO PERIMETER	1" = 1'-0"	16		TRELLIS KNEE BRACE	1" = 1'-0"	12		ROOF @ INT. WALL	1" = 1'-0"	8		CONC. FTG. @ POST	1" = 1'-0"	4

PLOT DATES DRAWN BY: JAU CHECKED BY: JAU DESIGNED BY: JAU REVISIONS: 1. REVISED 1 2. REVISED 2 3. REVISED 3 4. REVISED 4 5. REVISED 5 6. REVISED 6 7. REVISED 7 8. REVISED 8 9. REVISED 9 10. REVISED 10	
DESIGNER OF RECORD KURT E. GIUSTI RESIDENTIAL DESIGN & PLANNING BOX 128 FORESTVILLE, CA 95456 707.897.9552	
CLIENTS PHILIP AND SUSAN NIX 5985 LONE PINE ROAD SEBASTOPOL, CALIFORNIA 95472 BARN CONVERSION	DESCRIPTION DETAILS 8
ENGINEER OF RECORD SCOTT HUNTER Ph.D., P.E. 927 STEWART STREET #3 SANTA ROSA, CA 95404 707-528-6435	

DOOR SYMBOL


DOOR SCHEDULE

NO	TYPE	SIZE	SIDE LITE	HDRWR GROUP	CONST.	FINISH	RATING	FRAME	NOTE
1	C	3'-0"x6'-0"	NONE	A	MD. SOLID	PAINT	NONE	MD.	FR. DR. (TEMP.)
2	A	1'-0"x6'-0"	NONE	B	MD. SOLID	PAINT	NONE	MD.	
3	B	1'-0"x6'-0"	NONE	C	MD. HOLLOW	PAINT	NONE	WOOD	
4	C	(3) 3'-0"x6'-0"	NONE	D	MD. SOLID	PAINT	NONE	WOOD	FR. DR. (TEMP.)
5	D	(2) 2'-6"x6'-0"	NONE	E	MD. SOLID	PAINT	NONE	WOOD	FR. DR. (TEMP.)
6	B	2'-4"x6'-0"	NONE	F	MD. HOLLOW	PAINT	NONE	WOOD	POCKET DR.
7	E	2'-6"x6'-0"	NONE	G	MD. SOLID	PAINT	1 HR.	WOOD	AUTO CLOSER
8	F	(2) 4'-0"x6'-0"	NONE	D	MD. SOLID	PAINT	NONE	WOOD	FR. DR. (TEMP.)
9	G	3'-0"x6'-0"	NONE	A	MD. SOLID	PAINT	1 HR.	MD.	
10	H	(2) 4'-0"x7'-0"	NONE	H	FLYKD	PAINT	NONE	WOOD	FLYKD & 2X CONSTRUCTION
11	J	(4) 1'-4"x6'-0"	NONE	J	MD.	PAINT	NONE	MD.	

HARDWARE GROUPS

TYPE	LOCK/LATCH	BUTT	WEATHER STRIP	THRESH.	CLOSER	NOTE
A	LOCKSET/LATCHSET/DEADBOLT (3)	3-1/2X3	1/2 YES	MTL.	NONE	
B	LATCHSET/DEADBOLT	(2) 3X3	NONE	NONE	NONE	
C	LATCHSET	(2) 3X3	NONE	NONE	NONE	
D	LOCKSET	SLIDER	YES	MTL.	NONE	
E	PASSAGE	(3) 3X3	NONE	NONE	NONE	
F	FULL HANDLE/LATCH	NONE	NONE	NONE	NONE	POCKET TRACK
H	LOCKSET	(2) 4X12	NONE	NONE	NONE	* 2LD FASHIONED BARN DOOR STYLE HARDWARE
J	FULL HANDLE	(2) 2-1/2X2-1/2	NONE	NONE	NONE	BIFOLD LOUVERED DOORS / TO MEET VENTILATION REQ'S FOR PH.

DOOR TYPES




WINDOW SYMBOL


WINDOW SCHEDULE

NO	TYPE	SIZE	FRAME	GLAZING	FINISH	NOTE
1	A	3'-0"x5'-0"	WOOD	DUAL	NAT.	
2	A	3'-0"x6'-0"	WOOD	DUAL	NAT.	
3	A	3'-0"x6'-0"	WOOD	DUAL	NAT.	
4	A	3'-0"x5'-0"	WOOD	DUAL	NAT.	
5	A	3'-0"x5'-0"	WOOD	DUAL	NAT.	
6	A	3'-0"x6'-0"	WOOD	POCKET DR.	NAT.	
7	B	2'-0"x2'-0"	WOOD	DUAL	NAT.	
8	B	4'-0"x4'-0"	WOOD	DUAL	NAT.	
9	B	4'-0"x4'-0"	WOOD	DUAL	NAT.	
10	B	4'-0"x4'-0"	WOOD	DUAL	NAT.	
11	C	4'-0"x6'-0"	WOOD	DUAL	NAT.	6'-0" FIXED ABOVE / 1'-0" ANNING BELOW
12	A	3'-0"x5'-0"	WOOD	DUAL	NAT.	
13	D	2'-6"x2'-6"	WOOD	DUAL	NAT.	
14	D	2'-6"x2'-6"	WOOD	DUAL	NAT.	
15	D	2'-6"x2'-6"	WOOD	DUAL	NAT.	

WINDOW TYPES



PLOT DATES
DRAFT DAY
REVISED 1
REVISED 2
REVISED 3
REVISED 4
REVISED 5
REVISED 6
REVISED 7
REVISED 8
REVISED 9
REVISED 10
REVISED 11
REVISED 12
REVISED 13
REVISED 14
REVISED 15
REVISED 16
REVISED 17
REVISED 18
REVISED 19
REVISED 20
REVISED 21
REVISED 22
REVISED 23
REVISED 24
REVISED 25
REVISED 26
REVISED 27
REVISED 28
REVISED 29
REVISED 30
REVISED 31
REVISED 32
REVISED 33
REVISED 34
REVISED 35
REVISED 36
REVISED 37
REVISED 38
REVISED 39
REVISED 40
REVISED 41
REVISED 42
REVISED 43
REVISED 44
REVISED 45
REVISED 46
REVISED 47
REVISED 48
REVISED 49
REVISED 50



DESIGNER OF RECORD

KURT E. GIUSTI
RESIDENTIAL DESIGN & PLANNING
BOX 128
FORESTVILLE, CA 95456
707.887.8522

CLIENTS
PHILIP AND SUSAN NIX
5985 LONE PINE ROAD
SEBASTOPOL, CALIFORNIA 95472
BARN CONVERSION

ENGINEER OF RECORD


SCOTT HUNTER Ph.D. , P.E.
927 STEWART STREET #3
SANTA ROSA, CA 95404
707-526-6435

DESCRIPTION SHEET

SCHEDULES
9
SCALE: 1/4"=1'-0"
OF 13

SHEET NUMBERED NOTES

1. ARC-FAULT CIRCUIT INTERRUPTER REQUIRED AT BEDROOM BRANCH CIRCUITS. (GEG. 210-12-b)
2. PROVIDE SEPARATE 20 AMP CIRCUIT FOR BATHROOM RECEPTILES ONLY. OTHER BATHROOM ELECTRICAL ITEMS SHALL NOT BE ON THIS CIRCUIT.
3. PROVIDE INDIVIDUAL CONTROL VALVE OF PRESSURE BALANCE OR THERMOSTATIC MIXING VALVES TYPE TO SHOWER.
4. PROVIDE (2) 20A CIRCUITS FOR KITCHEN
5. PROVIDE (1) 20A CIRCUIT FOR LAUNDRY ROOM



ELECTRICAL PLAN

SCALE 1/4" = 1'-0"



PLOT DATES	
DATE	REVISION
11/11/04	1
11/11/04	2
11/11/04	3
11/11/04	4
11/11/04	5
11/11/04	6
11/11/04	7
11/11/04	8
11/11/04	9
11/11/04	10
11/11/04	11
11/11/04	12
11/11/04	13
11/11/04	14
11/11/04	15
11/11/04	16
11/11/04	17
11/11/04	18
11/11/04	19
11/11/04	20

DESIGNER OF RECORD

KURT E. GIUSTI

RESIDENTIAL DESIGN
& PLANNING

BOX 128
FORESTVILLE, CA 95456
707.897.8522

CLIENTS

PHILIP AND SUSAN NIX
5985 LONE PINE ROAD
SEBASTOPOL, CALIFORNIA 95472
BARN CONVERSION

DESCRIPTION ELECTRICAL/MECHANICAL PLAN

ENGINEER OF RECORD

SCOTT HUNTER Ph.D., P.E.

927 STEWART STREET #3
SANTA ROSA, CA 95404

707-526-6435

DESCRIPTION
ELECTRICAL /
MECHANICAL
PLAN

SHEET

10

SCALE
1/4" = 1'-0"

OF 18

[illegible]

Building Measures Checklist: Residential		Page 1 of 2	HF-19
NOTE: Low-voltage lighting subject to the Standard must contain three electronic components of the controller assembly and two wires of at least 14 AWG or approved by more stringent authority requirements listed on the Certificate of Compliance. When this checklist is incorporated into the permit document, the fixtures must not be considered to be approved as above compliance specifications for the mandatory measures. For the mandatory measures, the fixture must be in the assembly or on the checklist only.			
ACCOMPLISH		Check or Initial applicable boxes or enter N/A if not applicable.	REMARKS
Building Envelope Measures			
☐ EA	1904. Minimum R-value insulation		
☐	1905. Local (or manufacturer's) labeled R-value		
☐	1906. Minimum R-value in insulation in roof and attic or equivalent thickness in walls. Does attic have roof insulation? (If not, see 1904.)		
☐ EA	1907. Minimum R-13 rigid floor insulation in finished floors or equivalent.		
☐	1908. Total floor insulation - water storage tanks to greater than R-13, water vapor transmission rate to greater than 1.0 permits.		
☐ EA	1909. Insulation specified or installed meets insulation quality standards, (airtight joints and gaps).		
☐	1910. (Penetration Protection, Gasket Seals and Infiltration Control Goals)		
☐ EA	1911. Doors and windows (including doors and windows) specified or installed to meet or exceed:		
	1. Insulation properties (except fixed horizontal glass doors with certified U-factor, certified Solar Heat Gain Coefficient (SHGC) and Infiltration Certification).		
	1.1. Location doors and windows meet/minimum of all joints and penetrations sealed and sealed.		
☐	1912. Vapor barriers (mandatory in Climate Zones 3 and 4) or 3 mil.		
☐	1913. Special moisture barrier installed in compliance with Section 25 meets moisture vapor standards.		
☐	1914. Installation of Drainage, Drainage Gap System and Gas Tight.		
☐	1915. Airtight and Airtightness (Pressure Tight)		
	1. Complete airtight or gas tight		
	2. Airtight or gas tight with airtight and control		
	3. Airtight and control		
	4. No continuous burning gas plants allowed		
Space Conditioning, Water Heating and Plumbing System Measures			
☐ EA	1916. HVAC equipment, water heaters, furnaces and ducts certified by the Commission		
☐ EA	1917. Heating and/or cooling loads calculated in accordance with ASHRAE, RSI or ACCA		
☐ EA	1918. Strain Relief/Seal on all applicable heating and/or cooling systems		
☐	1919. Drip and Leak Insulation		
	1. Drip and leak water heater with air or energy factor less than 1.00 must be externally wrapped with insulation having no minimum thermal resistance of R-12 or greater		
	2. Electric tank water heater with air factor less than 1.00 must be externally wrapped with insulation having no minimum thermal resistance of R-12 or greater		
	3. Electric tankless water heater, without change tank, or other heated tankless water heater have R-12 external insulation or R-12 covered internal/external insulation.		
	4. All buried or exposed piping installed in restraining sections of hot water systems.		
	5. Cooling system piping less than 2 inches. If insulated		
	6. Any heating (hot water heating space) and indirect hot water tank.		
Prepared by:	By (Inspector):	Date: _____	Page: 1 of 2

DESCRIPTION	SHEET
TITLE 24	11
SCALE:	OF 1

WOOD FRAMING NOTES

MATERIALS

- Unless otherwise noted, all framing lumber shall be Douglas Fir and meet or exceed the following commercial grades:
Shuts, plates, blocking Standard or Better
Joists, rafters, ledgers, and 4x beams and posts No. 2
Exposed joists, rafters, ledgers, and 4x beams and posts No. 1
Beams and posts 4x and larger No. 1
- Wood shall have an average moisture content of 19 % at time of erection with no single member having a moisture content exceeding 22%.
- Wood in contact with foundation concrete or exposed to weather shall be pressure treated Douglas Fir (Uses Fir for 2 x 4, and 2 x 6) unless otherwise noted on plans.
Wood posts embedded in concrete or earth shall be pressure treated Douglas Fir and stamped for "Ground Contact Use".
a. All pressure treated lumber shall be clean, dry and free from surface residue.
b. Handle treated lumber and field treat penetration damage (i.e. cut ends, notches and berrings) in accordance with ANPA Standard M-4.
c. All pressure treated lumber shall be stamped with the ANPA's quality mark specifying "Above Ground Use" or "Ground Contact Use".
*A "Timber Products Inspection" quality mark is acceptable in lieu of the ANPA stamp for pressure treated Douglas Fir.
- While any ANPA or ICCO approved preservative is acceptable, we recommend CBA based preservative avoid the use of arsenic.
- Floor shall be sheathed with 23/32" min. TAG APA ratedplywood (OSB is not acceptable) 45/24, exposure 1 with face grain of sheathing applied perpendicular to joists. One with 1/4" OSB. Nail sheathing at 6" o.c. edges and 12" o.c. field, typical u.o.n. At areas where capel and post will be applied directly over the floor sheathing use TAG, APA ratedplywood Stud-I-Floor, 24" o.c., exposure 1.
- Walls shall be sheathed with 15/32" min. APA rated sheathing, 32/16, exposure 1. Nail sheathing at 6" o.c. edges and 12" o.c. field, typical u.o.n. See shear wall schedule.
- Roof shall be sheathed with 15/32" min. APA ratedplywood (OSB is not acceptable), 32/16, exposure 1, with face grain of sheathing applied perpendicular to rafters. Nail sheathing at 6" o.c. edges and 12" o.c. field typical u.o.n. Use ply clips at unlatched ply edges.
- Glue-lam beams shall be combination 24F-V4 (24F-V8) at continuous spans and centerlines) with 1800' radius camber at roots, 3000' radius camber at floors, unless otherwise noted on the drawings. Each beam shall be stamped by a grade mark or have a certificate of inspection issued by an approved agency. Furnish certification of inspection to the building department. Glue-lam beams shall conform to AITC 117-93.

NAILS & FASTENERS

- All nailing not specifically called out on the plans shall conform to USC Table 23-8-B-1.
- Nails shall be as follows for various applications:
a. 2x framing exposed to weather - Nails may be vinyl coated sinkers, common or electroplated box.
b. 2x framing exposed to weather - Nails shall be hot dipped galvanized.
c. Floor Sheathing - Nails shall be 8d deformed shank.
d. Wall Sheathing - See shear wall schedule for nail size. Nails shall be common, common shanks or hot dipped galvanized box. Sinkers and electroplated galvanized box nails may be used if the size is increased one size larger than specified on the schedule. Exterior sheathing exposed to weather shall use hot dipped galvanized box.
e. Roof Sheathing - Nails shall be 8d common, 8d sinker or 8d electroplated galvanized box nails.
f. All fasteners and other metal connectors - Size as specified by the manufacturer. Hot dipped galvanized nails shall be used where exposed to weather. Connections and fasteners in contact with pressure treated wood shall have minimum 2 Mil coating or equal, stainless steel or preferred.
3. Where wood tends to split, replace member and pre-drill holes.
4. Nails for wood structural sheathing shall be driven flush but shall not fracture the surface of the sheathing.
5. Joist hangers, metal connectors and other miscellaneous timber connectors shall be per Simpson Strong-Tie. Nail or bolt at all pre-drilled holes, per manufacturer's instructions unless otherwise noted. (At "No" hangers, use specified number of fasteners for maximum load).
6. Machine bolts and anchor bolts shall conform to ASTM A-307. Bolts, nuts and washers exposed to weather shall be hot dipped galvanized. Provide washers under head and nut where bearing is against wood. Bolt holes in wood shall be 1/16" larger than bolt size unless otherwise noted. Nuts shall be tightened when placed and retightened before drying in.

CONCRETE NOTES

- Concrete shall have a minimum compressive strength of 2500 psi at 56 days with minimum of cementitious material shall be Class (F) Fly Ash.
- Minimum reinforcing steel cover requirements:
a. Cast against and exposed to earth 3"
b. Formed surfaces 2"
3. Reinforcing steel shall conform to ASTM A-615, (including supplements B1), grade 60 for #5 bars and larger and grade 40 for #4 bars and smaller. Steel shall be kept clean and free of rust scales.
4. Reinforcing bars shall be in lengths as long as practicable. Reinforcing bars requiring bending in the field shall be "cold bent". All corners and intersections bars shall retain a minimum of 18". All bar laps shall have 24" laps minimum unless otherwise noted.
5. Reinforcing anchor bolts and inserts shall be rigidly held in place prior to placing concrete.
6. All footing excavations shall be neat. Over excavations in depth and width shall be filled with concrete. All loose soils shall be removed from excavations prior to placement of concrete.
7. Bump, Batten, Fending, and Plastic Sheeting are acceptable for required 7 day cure of slab. Side use of curbing compound is not acceptable.

FLOOR FRAMING NOTES

- See sheet S-1.1 for standard construction details.
- Nails for joists shall be between joists unless otherwise noted.
- Bearing walls below are shown shaded. Splice joists only at bearing walls.
- WALL FRAMING NOTES
- Unless otherwise noted on the structural or architectural plans all walls shall be framed with 2 x 4 (minimum) studs at 16" o.c. for wall heights up to 10 feet and 2 x 6 studs at 16" o.c. for walls greater than 10 feet high.
2. All studs shall be full height (continuous) pieces between supporting floors, ceilings, and roofs.
3. All headers shall be 4 x 12 DF #2 or 5 x 10 DF #1 for openings less than 4 feet unless otherwise noted.
4. 4 x 6 or 6 x 8 #2 for openings less than or equal to 4 feet unless otherwise noted.
Foundation cripple studs less than 14" high shall be solid blocked with double 2x blocks.
5. Posts indicated on framing plans are below unless otherwise noted. Post sizes are indicated on the highest level framing plan on which they occur.
6. Posts indicated but not called out are a minimum of 2 - 2x studs faced nailed with 16d at 16" o.c.
7. At floor levels, solid block in the joint space under all posts to the full width of the post.
8. Where top plates are notched or drilled to accommodate plumbing, flue, or ducts the top plates shall be spliced with Simpson HMA straps (unless a strap of greater tensile strength is indicated on the drawings).
9. Shear walls are indicated by hangers. See 1/SJ.1 for additional information.

ROOF FRAMING NOTES

- See sheet S-1.1 for standard construction details.
- Building has been designed for a maximum roofing material dead load of 5 psf.
- All roof openings shall be between rafters unless otherwise noted on the drawings.
- Bearing walls are shown shaded. Chuce parties, rafters, hips valleys, and ridge boards to bearing walls or beams only.
- California Framing shall be 2x8 rafters and 2x8 ridges and hips unless otherwise noted. (When California framing is typical framing below of 48" o.c. maximum. Typical roof framing and plywood sheathing shall be continuous below California framed areas. Provide solid blocks of continuous 2x2 member under ends of all rafters.
6. Shear walls are indicated by hangers and are below the level of framing shown U.O.N. See 1/SJ.1 for additional information.

INSTALLATION

- All carpentry shall conform to the conventional light-frame construction provisions of the USC section 2300 unless detailed otherwise.
- Solid block under all posts to provide continuous support to the foundation or post below.
- All beams shall be sued cut for full bearing.
- Do not notch beams, rafters, joists or studs except as noted on the plans or otherwise approved by the engineer.

STEEL

MATERIALS

- Steel plates shall conform to ASTM A36.
- Weld metal shall match base metal with a minimum of 70 ksi.
- All steel exposed to wet conditions shall be galvanized.
- Bolts shall be A307 unless otherwise noted on the drawings. Bolts shall conform to ASTM A307 Grade A, except steel externally threaded standard fasteners. All bolts shall be new and shall not be reused.

GEOTECHNICAL NOTES

- The Engineer has not made a subsurface investigation of the building site and is not responsible for general site stability or soil suitability for the proposed project. A review by a soil engineer or geologist may be desirable by the owner.
- Foundation design is based on the maximum soil pressures as set forth in Table 18-A of the USC chapter 18. The design assumes a class 5 soil with an allowable soil bearing pressure of 1000 psf with a constant compression index less than 20.
- All foundations shall bear on firm, undisturbed, native soils or engineered fills at or exceeding depths shown on the drawings.
- All footing excavations shall be neat. Over excavations in depth and width shall be filled with concrete. All loose soils shall be removed from excavations prior to placement of concrete.
- Bottom of footings shall be stepped where slope exceeds 1:10. Top of stem wall to be stepped unless otherwise noted.

SHEAR WALL SCHEDULE			
SYMBOL	SHEATHING & EDGE NAILING	ANCHOR BOLTS	REMARKS
⊖	15/32" APA SHGT. 32/16 @ 6" o.c.	5/8" @ 48" o.c.	TYPICAL @ EXTERIOR WALLS U.O.N.
⊕	15/32" APA SHGT. 32/16 @ 4" o.c.	5/8" @ 32" o.c.	
⊗	15/32" APA SHGT. 32/16 @ 6" o.c.	5/8" @ 32" o.c.	NOTE A 3x SILL
⊙	15/32" APA SHGT. 32/16 @ 2" o.c.	5/8" @ 24" o.c.	NOTE A 3x SILL

TYPICAL NOTES:

- All wood structural sheathing shall be APA rated Sheathing exposure 1" with a minimum panel index of (32/16) unless otherwise noted.
- Studs shall be at 16" o.c. maximum.
- Field nailing for all wood panel(s) shall be @ 12" o.c.
- Block and nail at wood panel(s) edges.
- All wood panel(s) edges shall be spliced at centerline of framing or blocking.
- Block and nail @ 12" o.c.
- See detail 2/SJ.1 for typical shear wall details.
- All nails shall be per "Nails & Fasteners" Note 2d.

SPECIAL NOTES:

REQUIRED WHEN FLY EDGE NAILING IS AT 3" o.c. OR TIGHTER OR WHEN PLYWOOD IS INSTALLED ON BOTH SIDES OF THE WALL.
A. AT WOOD PANEL JOINTS, USE 3x MINIMUM STUDS, PLATES AND BLOCKING. STAGGER NAILS.

DESIGN CRITERIA:

VERTICAL LOADS		DEAD LOAD (DL)	LIVE LOAD (LL)
ROOF		12 psf	16 psf
FLOOR		15 psf	50 psf
FOUNDATION		- "ALLOWABLE SOIL BEARING PRESSURE"	
1) DL + LL:		1,000 psf	
2) DL + LL + WIND/SEISMIC:		1,337 psf	
LATERAL LOADS			
SEISMIC WIND	14 WOL RUMPL	ZONE: 4	ZONE: C

GENERAL STRUCTURAL NOTES

- All work shall be in compliance with the uniform Building Code, latest edition adopted by the local governing agency and any applicable local ordinances.
- The contractor shall notify the architect of any discrepancies on the drawings requiring clarification or revisions before commencing with the work.
- Drawings shall not be scaled. All dimensions shown on the plans shall be verified by the contractor prior to commencing work and any discrepancies shall be brought to the attention of the architect.
- See architectural drawings for all wall locations and dimensions unless otherwise noted.
- Details not specifically shown shall be of the same nature as other similar conditions.
- Structural design or review of temporary shoring, additional reinforcing, bracing, form work, scaffolding, erection methods, etc. shall be the responsibility of the contractor.
- Shop drawings are an aid for field placement and are supervised by the structural drawings. It shall be the responsibility of the general contractor to make certain that all construction is in full agreement with latest approved structural drawings.

EXISTING CONDITIONS

- Existing structural elements shown on these drawing represent assumptions based on existing drawings (if available), documentation by others, and known construction practices. The Engineer does not warrant that these conditions are representative of those existing. The owner and contractor shall investigate existing conditions prior to start of construction.
- Where drawings indicate existing (E) conditions, or verify in field (V.I.F.), it is required that the contractor maintain and provide new materials to create such conditions, or notify the designer of conflicting conditions.
- The contractor shall immediately inform the designer if visual observation or demolition exposes conditions that conflict with the design.
- The owner or contractor shall inform the local governing agency if visual inspection or demolition reveals hazardous material in any form of the project site.
- The contractor is responsible for the design and erection of all temporary bracing required during construction.

NIX RESIDENCE

5985 LOWE PINE RD.
SEBASTOPOL, CA 95472

Approved: _____
Signature Order

Scott Hunter Ph.D., P.E.
Consulting Engineer

627 Howard Street #3
Sebastopol, CA 95472
Phone: 707 526-6435
Fax: 707 526-6435
Email: SHPE@scott.net

DATE: 5/11/04


DRAN BY: SH

SCALE: 1/8"=1'-0"


PROJECT NUMBER: 00000000

SCHEDULES,
DESIGN CRITERIA
AND
FRAMING NOTES


S 1.0




10 HOLDOWN




7




8




a




d




e




c



4 PLY NAILING @ RIM JST.




5




6

* FOR POSTS @ END OF SHEAR WALLS REFER TO DETAIL 2 B.


HOLDDOWNS	SDS SCREWS, BOLTS, NAILS	ANCHOR BOLT	'X'	'Y'
PHD2	10 - SDS 1/4X3	SSTB16	5/8" DIA	1.375" 12"




1




a




b



c



d




e

TYP. PLYWOOD JOINT

REVISIONS:
△
△
△

Nix Residence
3985 Lane Pine Rd.
Redwood City, CA 94061
Barn Conversion



227 Shawan Street #2
Santa Rosa, CA 95404
Phone: 707 526-4438
Fax: 707 526-4435
Email: SHPE@snrc.net

DATE	DRAWN
SCALE	JOB
SHEET	

S 1.1

Printed on: 5/20/04